

Switch 24 porturi PoE 100Mbps, 2 port uplink Gigabit, SMART Management - HIKVISION

DS-3E1326P-EI



Switch-ul DS-3E1326P-EI de la Hikvision are urmatoarele caracteristici:

- Standarde: Conform cu standardele Ethernet IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab si IEEE802.3z;
- Standarde PoE: IEEE 802.3at/af pentru porturile PoE;
- Transmisie extinsa: Suporta transmisie pe distante de pana la 300 m;
- Performanta: Forwarding la viteza maxima si comutare tip store-and-forward;
- Management inteligent: Monitorizare topologie retea, notificari alarme si monitorizare sanatate retea;
- Constructie durabila: Carcasa metalica de inalta rezistenta.
- Producator **HIKVISION**
- Numar porturi PoE **24 porturi 10/100Mbps**
- Porturi Uplink **2 x RJ45 10/100/1000Mbps, 2 x SFP 1000 Mbps (combo)**
- Capacitate switch **8.8 Gbps**
- Management **Network topology management, alarm push, network health monitor, Video Control and Preview;**
- Putere PoE **total 370W - 15.4W/port, max. 30W/port**

- Standard PoE **IEEE 802.3af, IEEE802.3at**
- Mod functionare **Standard (100m) / mod EXTENDED (300m)**
- Protectie **ESD, descarcari electrice, anti-interferente**
- Tensiune alimentare **100~240 V AC**
- Consum **max. 400W**
- Temperatura operare **-10° ~ +55 °C**
- Dimensiuni **440 × 44 × 221 mm (1U rakabil)**
- Greutate **2.83 Kg.**