


## DESCRIPTION

S/FTP CAT.6 cable 23 AWG Bare Coppe, manufactured according to ISO / IEC 11801, EIA / TIA-568-C.2, EN-50173.

## TECHNICAL SPECIFICATIONS

Conductor	Bare copper 0,565+/- 0,01 mm
Insulation	HDPE 1,30+/-0,05 mm
Identification of pairs	
1 pair	Blue - White / Blue
2 pair	Orange - White / Orange
3 pair	Green - White / Green
4 pair	Brown - White / Brown
Screening material	Aluminum foil each pair
Braid	Aluminum braid Coverage ≥65%
Sheath	LSZH
Color	Blue
Bending radius	≥ 8 x Diameter (mm) Installation
Storage temperature	-15°C + 70°C



## ELECTRICAL CHARACTERISTICS

n° Pairs.xΦmm	Conductor Resistance Ω/km	Resistance Unbalance	Cap. between cond. pair pF / m	Velocity of Propagation %	Impedance Ω	ΦExt. (Appvox) mm
4x2x0,565	max.73.5	max.4%	/	69	100±15	7,0+/-0,3

Frequency (MHz)	RL ≥dB	ATT ≤dB/100m	NEXT ≥dB	DELAY ≤ns/100m	PS NEXT ≥dB	EL FEXT ≥dB/100m	PS EL FEXT ≥dB/100m
1	20.0	2.03	74.3	570.00	72.3	67.8	64.8
4	23.0	3.78	65.3	552.00	63.3	55.8	52.8
8	24.5	5.32	60.8	546.73	58.8	49.7	46.7
10	25.0	5.95	59.3	545.38	57.3	47.8	44.8
16	25.0	7.55	56.2	543.00	54.2	43.7	40.7
20	25.0	8.47	54.8	542.05	52.8	41.8	38.8
25	24.3	9.51	53.3	541.20	41.3	39.8	36.8
31.25	23.6	10.67	51.9	540.44	49.9	37.9	34.9
62.5	21.5	15.38	47.7	538.55	45.4	31.9	28.9
100	20.1	19.80	44.3	537.60	42.3	27.8	24.8
200	18.0	29.98	39.8	536.54	37.8	21.8	18.8
250	17.3	32.85	38.3	536.27	36.3	19.8	16.8

## PACKING

305m in wooden drum.  
500m in wooden drum.

