

FPA1700

Terminal de control access
si pontaj, IP, rezistent la apa

DESCRIERE

FPA1700 este terminal de control access si pontaj, cu conectivitate IP, rezistent la apa (IP65). Identificarea utilizatorilor se poate face cu amprenta sau card (EM4100).

CARACTERISTICI

- 1500 amprente
- 10.000 cartele
- 30.000 de tranzactii
- Comunicatie IP, RS485, USB, Wiegand I/O, Webserver
- Tastatura cauciuc
- Buton iesire, sonerie, alarma, senzor usa, yala electrica
- Caracasa ABS
- Rezistent la apa (IP65)
- Verificare amprenta 1:N $\leq 2s$ (N=1500), 1:1 $< 1s$
- FRR $< 1\%$, FAR $\leq 0.0001\%$

SPECIFICATII

- LCD 128x64 OLED, alb
- CPU 400MHz
- Memorie 128MB Flash + 32 MB RAM
- Linux OS
- Senzor amprente 500DPI
- Tensiune de alimentare - 12Vcc, 3A
- Distanța de citire: 3-6 cm
- Temperatura: -20°C ~ 50°C
- Dimensiuni: L62.5mm x W185mm x H41.5mm.
- Greutate: 380g



Fisa tehnica