


## DESCRIPTION

Manufactured according to ISO / IEC 11801, EIA / TIA 568B, EN-50173.

## TECHNICAL SPECIFICATIONS

Conductor	Bare copper 0,52+/- 0,005 mm
Insulation	HDPE 0,92+/-0,05 mm
Identification of pairs	
1 pair	Blue - White / Blue
2 pair	Orange - White / Orange
3 pair	Green - White / Green
4 pair	Brown - White / Brown
Sheath	PVC
Color	Grey
Bending radius	≥ 8 x Diameter (mm) Installation
Storage temperature	-15°C + 70°C



## ELECTRICAL CHARACTERISTICS

Type (n° Pairs. x AWG)	Conductor Resistance Ω/km	Resistance Unbalance	Cap. between cond. pair pF / m	Velocity of Propagation %	Impedance Ω	ΦExt. (Appvox) mm
4x2x24	max.87.0	max.5%	56	67	100+/-15	5,10+/-0,3

Frequency (MHz)	RL ≥dB	ATT ≤dB/100m	NEXT ≥dB	DELAY ≤ns/100m	PS NEXT ≥dB	EL FEXT ≥dB/100m	PS EL FEXT
1	20.0	2.1	65.3	570.00	62.3	63.8	60.8
4	23.0	4.1	56.3	552.00	53.3	51.8	48.8
8	24.5	5.8	51.8	546.73	48.8	45.7	42.7
10	25.0	6.5	50.3	545.38	47.3	43.8	40.8
16	25.0	8.2	47.2	543.00	44.2	39.7	36.7
20	25.0	9.3	45.8	542.05	42.8	37.8	34.8
25	24.3	10.4	44.3	541.20	41.3	35.8	32.8
31.25	23.6	11.7	42.9	540.44	39.9	33.9	30.9
62.5	21.5	17.0	38.4	538.55	35.4	27.9	24.9
100	20.1	22.0	35.3	537.60	32.3	23.8	20.8

## Packing

305m in pull box

